



Application for Weld	Procedure Qualification Testing
Client Name:	
Client Contact Name:	
Client Address:	
Email:	
Phone:	
Date of Enquiry	

This is an agreement between **NECIT Services Ltd** (us, we, the certified body) And:

The applicant (you, The Client)

By the completing and submitting of this application the Client is requesting NECIT Services Ltd to attend site and undertake witnessing and subsequent testing of welded items in line with our Scheme NECIT-QM-002. Successful completion of the process will result in either the qualification of Company Welding Procedures in accordance with our ISO 17020 accreditation and/or the qualification of Company Welders in accordance with our ISO 17024 accreditation.

Any requirements for Non-destructive Testing (NDT) will be provided by an ISO 9712 level 2 technician working to procedures Approved by a level 3 technician.

All mechanical testing will be undertaken by an approved NECIT supplier holding a UKAS accreditation under ISO 17025 whose schedule of accreditation if suitable for the testing which is required by the standard.

You agree to provide us with all necessary information as required in this document in order for us to proceed with the witnessing and testing. All information required is specified in the attached application forms which must be returned to us before the date of the planned assessment. If there are any requirements for special requests these should be included in the application forms.

NECIT Services Ltd will only recognise results obtained by calibrated equipment owned by ourselves or our approved suppliers. Should an External provider of NDT or Mechanical testing be used, a NECIT Services Witness shall be present to verify results.

Government issued Photographic ID for each candidate will be required as per the scheme. Failure to provide government issued Photo ID (Passport, Driving licence etc) will mean that we are unable to proceed with the examination and costs may be incurred.

It is your duty to notify of us any changes which may affect the validity of this application and any subsequent qualifications/certifications. Failure to do so may result in legal action being taken by interested parties.

All certificates issued under the scheme remain the sole property of NECIT Services Ltd. The right to withdraw, suspend or alter the certification at any point remains at our discretion.

All certificates will be held until full payment is received or credit terms have been agreed. None payment will result in withdrawal of certificates.

Any queries please contact the Technical Manager Certification@necitservices.com or in writing details of which can be found on our website www.necitservices.com





Procedure Qualification Order Details

The below information is required to book a Third Party Welding Examiner. The answers to the below should be the details of what you intend to conduct during the witnessing, We understand that during testing things may change, however we must understand the fundamental intentions of the

If unsure of any required answers, please call NECIT Certification department.

You are required to submit a	WPQR Or	der form for Each	WPQR.					
Dates For Witnessin	g							
Preferred Date								
Number of days Req	uired							
WPQR Identification								
pWPS/WPS Number					e send copy with t			
WPQR Number				Please	e note this referen	ice will be oi	n all Traceable docu	umentation for WPQR
Applicable Standard	S							
Testing Standard		ISO 1	5614-1 🗆	ISO 15614-2	2□ ISO 156	513□	ASME IX □	AWS D1.1 □
Additional standard	if	ISO 1	5614-1 □	ISO 15614-2	2□ ISO 156	513□	ASME IX □	AWS D1.1 □
applicable								
Client Specification	or Code	e of					Please send copy	with this form
Practice						_	,,	
Application Standard								
PESR 2016 or PED C	ertifica	ition		Yes □			No	
Required?								
Welding Processes	& Posit	tions						
	мма	111 🗆						
Welding process:	SAW	121 🗆	122 🗆	124 □	125□	126 □		
*EN ISO 4063	MIG/						100 □	
	MAG	131 □	132 □	133 □	135 □	136 □	138 🗆	
	TIG	141 🗆	142 □	143 □	145 🗆	146 □	147 □	
	Other					50,00		
Welding		PA/1G □		PB □		PC/2G		PD □
Position(s) for		PE/4G □		PF/3G □		PG/3G		
testing: *EN ISO 6947/AWS		PH/5G □		PJ/5G □		PK □		
	F	H-LO45/6G □	F	1-L045/6G (R)) 🗀 .	J-L045/6	oG 🗆	
Are your Welding Processes	M	1anual □	Mec	hanised/Auto	matic/Robotic			
1 10003003								
Parent Material Deta				1. 1. 1 T		T	0'-	1. 0
Side		.or 🗆		Joint Typ	e			le 2 e □ Other □
Pipe ☐ Plate Material Grade*	⊔ Utr	ner 🗆	Ru# □ T	· Rutt □ Rran	ch ☐ Fillet ☐	Mate	Pipe Plate	e 🗆 Other 🗆
Diameter (mm)				Please add			neter (mm)	
Thickness (mm)			Other L	(i icase ada	detail below)		kness (mm)	
Filler Material						10		1
Grade(s)*								
Additional								
Information								

^{*}Parent material Certificates and Consumable welding wire certificates are required for certification, Please send a copy.





Post Weld Heat Treatment		
Is PWHT Required?	Yes □	No □
NECIT to arrange PWHT?	Yes □	No □
Heating Rate (°C/hr)		
Holding Temp (°C)		
Holding Time		
Cooling Rate (°C/hr)		
* If, yes provide PWHT Location and	date as witnessing is required	
ii, yes provide i wiii Location and	radic as withessing is required	
Non-Destructive Testing		
NECIT to arrange NDT?	Yes □	No □
Inspection / Quality Level		
Minimum hold period between	een welding and NDT	
NECIT as an ISO 17020 Insp	pection body, shall conduct Non-Destructive	ve Testing to the minimum requirements of the
		itional NDT Conducted, Please Detail below
* If, No provide NDT Location and da	ate as witnessing is required. Copies of NDT Proced	ures endorsed by ISO 9712 Level 3 shall be
	ed by a technician certified to a minimum level of IS	
,	•	
Machanical Testing		
Mechanical Testing	nol testing?	No □
NECIT to arrange Mechanic	-	No □
NECIT to arrange Mechanic	ormation relating to your WPQR mechanic	cal testing Criteria
NECIT to arrange Mechanic Please provide specific info	-	cal testing Criteria Guidance
NECIT to arrange Mechanic	ormation relating to your WPQR mechanic	Cal testing Criteria Guidance - The tensile strength of the test specimen
NECIT to arrange Mechanic Please provide specific info	ormation relating to your WPQR mechanic	cal testing Criteria Guidance - The tensile strength of the test specimen shall not be less than the corresponding
NECIT to arrange Mechanic Please provide specific info	ormation relating to your WPQR mechanic	Cal testing Criteria Guidance - The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent
NECIT to arrange Mechanic Please provide specific info	ormation relating to your WPQR mechanic	cal testing Criteria Guidance - The tensile strength of the test specimen shall not be less than the corresponding
NECIT to arrange Mechanic Please provide specific info	ormation relating to your WPQR mechanic	Cal testing Criteria Guidance - The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent
NECIT to arrange Mechanic Please provide specific info	ormation relating to your WPQR mechanic	cal testing Criteria Guidance - The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to
NECIT to arrange Mechanic Please provide specific info	ormation relating to your WPQR mechanic	cal testing Criteria Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing.
NECIT to arrange Mechanic Please provide specific info	ormation relating to your WPQR mechanic	cal testing Criteria Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum
NECIT to arrange Mechanic Please provide specific info	ormation relating to your WPQR mechanic	cal testing Criteria Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum value specified for the parent material
NECIT to arrange Mechanic Please provide specific info Min Tensile (MPa)	Requirement	cal testing Criteria Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum value specified for the parent material having the lowest tensile strength.
NECIT to arrange Mechanic Please provide specific info	Requirement	cal testing Criteria Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum value specified for the parent material having the lowest tensile strength. Can be found on the Parent material
NECIT to arrange Mechanic Please provide specific info Min Tensile (MPa)	Requirement	cal testing Criteria Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum value specified for the parent material having the lowest tensile strength. Can be found on the Parent material Certificate unless specified by Customer
NECIT to arrange Mechanic Please provide specific info Min Tensile (MPa) Impact Test Temperature (Requirement	cal testing Criteria Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum value specified for the parent material having the lowest tensile strength. Can be found on the Parent material Certificate unless specified by Customer specification or contract requirements
NECIT to arrange Mechanic Please provide specific info Min Tensile (MPa) Impact Test Temperature (Max Hardness (HV10)	Requirement	cal testing Criteria Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum value specified for the parent material having the lowest tensile strength. Can be found on the Parent material Certificate unless specified by Customer specification or contract requirements ISO 15614-1 Table 3
NECIT to arrange Mechanic Please provide specific info Min Tensile (MPa) Impact Test Temperature (Requirement	cal testing Criteria Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum value specified for the parent material having the lowest tensile strength. Can be found on the Parent material Certificate unless specified by Customer specification or contract requirements ISO 15614-1 Table 3 If non Standard joint, Please advise of the
NECIT to arrange Mechanic Please provide specific info Min Tensile (MPa) Impact Test Temperature (Max Hardness (HV10)	Requirement	cal testing Criteria Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum value specified for the parent material having the lowest tensile strength. Can be found on the Parent material Certificate unless specified by Customer specification or contract requirements ISO 15614-1 Table 3 If non Standard joint, Please advise of the joint design which assists the laboratory in
NECIT to arrange Mechanic Please provide specific info Min Tensile (MPa) Impact Test Temperature (Max Hardness (HV10)	Requirement	cal testing Criteria Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum value specified for the parent material having the lowest tensile strength. Can be found on the Parent material Certificate unless specified by Customer specification or contract requirements ISO 15614-1 Table 3 If non Standard joint, Please advise of the joint design which assists the laboratory in interpretation.
NECIT to arrange Mechanic Please provide specific info Min Tensile (MPa) Impact Test Temperature (Max Hardness (HV10) Macro Specific Info	ormation relating to your WPQR mechanic Requirement OC)	cal testing Criteria Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum value specified for the parent material having the lowest tensile strength. Can be found on the Parent material Certificate unless specified by Customer specification or contract requirements ISO 15614-1 Table 3 If non Standard joint, Please advise of the joint design which assists the laboratory in interpretation. Depth of Penetration Requirements
NECIT to arrange Mechanic Please provide specific info Min Tensile (MPa) Impact Test Temperature (Max Hardness (HV10) Macro Specific Info	Pection body, shall conduct Non-Destructiv	Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum value specified for the parent material having the lowest tensile strength. Can be found on the Parent material Certificate unless specified by Customer specification or contract requirements ISO 15614-1 Table 3 If non Standard joint, Please advise of the joint design which assists the laboratory in interpretation. Depth of Penetration Requirements of the
NECIT to arrange Mechanic Please provide specific info Min Tensile (MPa) Impact Test Temperature (Max Hardness (HV10) Macro Specific Info	Pection body, shall conduct Non-Destructiv	cal testing Criteria Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum value specified for the parent material having the lowest tensile strength. Can be found on the Parent material Certificate unless specified by Customer specification or contract requirements ISO 15614-1 Table 3 If non Standard joint, Please advise of the joint design which assists the laboratory in interpretation. Depth of Penetration Requirements
NECIT to arrange Mechanic Please provide specific info Min Tensile (MPa) Impact Test Temperature (Max Hardness (HV10) Macro Specific Info	Pection body, shall conduct Non-Destructiv	Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum value specified for the parent material having the lowest tensile strength. Can be found on the Parent material Certificate unless specified by Customer specification or contract requirements ISO 15614-1 Table 3 If non Standard joint, Please advise of the joint design which assists the laboratory in interpretation. Depth of Penetration Requirements of the
Min Tensile (MPa) Impact Test Temperature (Max Hardness (HV10) Macro Specific Info NECIT as an ISO 17020 Inspapplicable WPQR or Applica	Pection body, shall conduct Non-Destructiv	Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum value specified for the parent material having the lowest tensile strength. Can be found on the Parent material Certificate unless specified by Customer specification or contract requirements ISO 15614-1 Table 3 If non Standard joint, Please advise of the joint design which assists the laboratory in interpretation. Depth of Penetration Requirements of the
Min Tensile (MPa) Impact Test Temperature (Max Hardness (HV10) Macro Specific Info NECIT as an ISO 17020 Inspapplicable WPQR or Applica	Pection body, shall conduct Non-Destructiv	Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum value specified for the parent material having the lowest tensile strength. Can be found on the Parent material Certificate unless specified by Customer specification or contract requirements ISO 15614-1 Table 3 If non Standard joint, Please advise of the joint design which assists the laboratory in interpretation. Depth of Penetration Requirements of the
Min Tensile (MPa) Impact Test Temperature (Max Hardness (HV10) Macro Specific Info NECIT as an ISO 17020 Inspapplicable WPQR or Applica	Pection body, shall conduct Non-Destructiv	Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum value specified for the parent material having the lowest tensile strength. Can be found on the Parent material Certificate unless specified by Customer specification or contract requirements ISO 15614-1 Table 3 If non Standard joint, Please advise of the joint design which assists the laboratory in interpretation. Depth of Penetration Requirements of the
Min Tensile (MPa) Impact Test Temperature (Max Hardness (HV10) Macro Specific Info NECIT as an ISO 17020 Inspapplicable WPQR or Applica	Pection body, shall conduct Non-Destructiv	Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum value specified for the parent material having the lowest tensile strength. Can be found on the Parent material Certificate unless specified by Customer specification or contract requirements ISO 15614-1 Table 3 If non Standard joint, Please advise of the joint design which assists the laboratory in interpretation. Depth of Penetration Requirements of the
Min Tensile (MPa) Impact Test Temperature (Max Hardness (HV10) Macro Specific Info NECIT as an ISO 17020 Inspapplicable WPQR or Applica	Pection body, shall conduct Non-Destructiv	Guidance The tensile strength of the test specimen shall not be less than the corresponding specified minimum value for the parent metal unless otherwise specified prior to testing. For dissimilar parent metal joints, the tensile strength shall not be less than the minimum value specified for the parent material having the lowest tensile strength. Can be found on the Parent material Certificate unless specified by Customer specification or contract requirements ISO 15614-1 Table 3 If non Standard joint, Please advise of the joint design which assists the laboratory in interpretation. Depth of Penetration Requirements of the



Premium Testing



* If, No provide Mechanical test lab Location and date as witnessing is required. Laboratory must be UKAS Accredited to ISO 17025 with scope of accreditation applicable to the required testing.

Type of Test PWHT NDT (VT/PT/MT/UT) Mechanical Testing	Same Day Results N/A □ □	s 24 Hours		48 Hours
Certification Preferences				
Electronic *£10 admin charge per paper cert issued Do you require a Welder Qualification	Paper □*	Yes □	Both □*	No □

Please complete NECIT-FRM 037b

NECIT Are able to offer quotations for Premium testing options detailed below. The below are on application only and do not come standard and must